


- Very Compact
- Low Cost
- 3 Motor Speed Options
- Various Tube Materials/Sizes
- 2 or 4 Rollers
- Integral Tube Grips



The 100 series, micro range of peristaltic pumps offer a low cost, compact & reliable means of dosing a wide range of liquids. They are available in various configurations of tubing type & size giving flow rates of between 0.016 & 0.26 ml/rev. The pump head is designed to be disposable but is assembled using a single screw enabling dis-assembly & re-assembly for tube changing if required. Important: These pumps are not suitable for use in wet or high humidity areas and should be fitted by a suitably qualified person.

DIMENSIONS (mm)



Williamson Manufacturing Co Ltd Unit 5, Lady Bee Industrial Estate Albion Street Southwick West Sussex BN42 4EP UK Email: sales@wmcpumps.com


www.wmcpumps.com

+44(0)1273 857752

New 100 series pump head only



UK manufacturers of quality peristaltic pumps



102-015-230-016/4 Example product code for 100 series pump head fitted with Viton® tubing , 15 RPM, 230v AC, 1.6mm ID tubing & 4 rollers


Motor specifications: 50/60Hz 5w. Dielectric strength 2000v AC 1 sec. Insulation Class E. Reliability 5 x 10⁶ Starts(min)

	Product Code
Pump Series and Tube Material	
Silicone	100
Tygon [®] A60F Norprene	101
Viton®	102
Tygon Chemical [®] Norprene (3mm tube size only)	107
Motor Speed RPM (based on 50Hz)	
8	-008
15	-015
30	-030
AC Voltage	
115v (minimum order quantity of 48 units)	-115
230v	-230
Tube Size (bore) mm	
0.8	-008
1.6	-016
3.0	-030
Number of rollers	
2	/2
4	/4

Materials of construction

Body & Back Plate	Rotor	Rollers	Bracket
SAN	POM	Stainless Steel	Zintec

Flow Rates ml per revolution



Williamson Manufacturing Co Ltd Unit 5, Lady Bee Industrial Estate **Albion Street Southwick** West Sussex BN42 4EP UK Email: sales@wmcpumps.com