

ALL FLOW RATES ARE MILLILITRES PER REVOLUTION

1.6mm BORE TUBE	TUBE MATERIAL		
No of Rollers	SILICONE	TYGON A60F®	VITON®
2	0.22	0.19	0.17
3	0.20	0.17	0.15
4	0.17	0.13	0.12
6	0.14	0.1	0.09

3.0mm BORE TUBE	TUBE MATERIAL			
No of Rollers	SILICONE	TYGON A60F®	VITON®	TYGON CHEMICAL®
2	0.64	0.58	0.52	0.53
3	0.59	0.54	0.45	0.47
4	0.5	0.46	0.37	0.39
6	0.32	0.3	0.26	0.27

5.0mm BORE TUBE	TUBE MATERIAL			
No of Rollers	SILICONE	TYGON A60F®	VITON®	TYGON CHEMICAL®
2	1.32	1.19	1.06	1.05
3	1.18	1.08	0.9	0.9
4	0.94	0.88	0.74	0.74
6	0.6	0.53	0.51	0.51

NOTE: FLOW RATES FOR GUIDANCE ONLY AS THEY ARE AFFECTED BY TOLERANCES, TEMPERATURE, PRESSURE & VISCOCITY

The Williamson Manufacturing Company Ltd provides no warranty on usage of pumps. We recommend that life tests be carried out prior to use. This information is given in good faith and believed to be correct at the time of publishing. The Williamson Manufacturing Company Ltd cannot accept responsibility for inaccuracy or any errors contained herein. Copyright the Williamson Manufacturing Company Ltd 2008.

Williamson Manufacturing Co Ltd
Unit 5
Lady Bee Industrial Estate
Southwick
West Sussex BN42 4EP UK
Email: sales@wmc pumps.com